

Series 500 Single Hung

CSI Division 08 51 13 - Aluminum Windows

12805 E. 31st St.
Tulsa, OK 74146
Phone: (800) 259-7580
Fax: (918) 665-2197

Style • Quality • Performance

Standard Features

- Sealed 7/8-in. insulated glass for optimum thermal efficiency
- High-density pile weatherstripping with mylar fin
- 14 standard powder coat colors
- Full range of Anodized and AAMA 2605 finishes available
- Fully operational lower sash tilts inward
- Sloped sill to promote water runoff
- Center cam locks plus hidden security locks
- Carbon steel spiral sash balances
- 2 5/8" and 3 1/4" frame depths available
- Interlocking meeting rails
- Extruded aluminum screen

Performance

- AAMA Rating: CW-PG30 Size: 56x91
- Air Infiltration (CFM): 0.1
- Water Resistance (PSF): 6.75
- Structural (PSF): 67.5
- STC range: 34-36
- *U-Factor: .47 / .39
- *SHGC: .29 / .27
- *VT: .52 / .47
- CRF: 50 / 57

*NFRC simulation results from certified testing labs.
Variety of glazing combinations available.



The Acadia Metropolitan Park
Arlington, VA
Dark Gray Powder Coat



Eden Street Apartments
Baltimore, MD
Essex Green Special Powder Coat



Solaire Wheaton Apartments
Silver Spring, MD
Bronze Powder Coat