

Series 515 Single Hung

CSI Division 08 5110 - Aluminum Windows

12805 E. 31st St.
Tulsa, OK 74146
Phone: (800) 259-7580
Fax: (918) 665-2197

Style • Quality • Performance

Standard Features

- Sealed 7/8-in. insulated glass for optimum thermal efficiency
- High-density pile weatherstripping with mylar fin
- 14 standard powder coat colors
- Full range of Anodized and AAMA 2605 finishes available
- Fully operational lower sash tilts inward
- Sloped sill to promote water runoff
- Center cam locks plus hidden security locks
- Carbon steel spiral sash balances
- 2 5/8" and 3 1/4" frame depths available
- Interlocking meeting rails
- Extruded aluminum screen

Performance

- AAMA Rating: CW-PG-50 Size: 56x91
- Air Infiltration (CFM): 0.07
- Water Resistance (PSF): 9
- Structural (PSF): 75
- STC range: 30-36
- *U-Factor: .47 / .39
- *SHGC: .29 / .27
- *VT: .51 / .46
- CRF: 50 / 57

*NFRC simulation results from certified testing labs.
Variety of glazing combinations available.



Bixby Northeast Elementary
Bixby, OK
Fluoron Green Kynar



Howard St. Station Apartments
Evanston, IL
Light Gray Powder Coat



Transylvania University Dorm
Lexington, KY
White Powder Coat