

## Series 525 Horizontal Slider

CSI Division 08 51 13 - Aluminum Windows

12805 E. 31st St.  
Tulsa, OK 74146  
Phone: (800) 259-7580  
Fax: (918) 665-2197

### Style • Quality • Performance

#### Standard Features

- Sealed 7/8-in. insulated glass for optimum thermal efficiency
- High-density pile weatherstripping with mylar fin
- 14 standard powder coat colors
- Full range of Anodized and AAMA 2605 finishes available
- Center cam locks plus hidden security locks
- Bronze rollers in nylon housing
- 2 5/8" and 3 1/4" frame depths available
- Interlocking meeting rails
- Extruded aluminum screen

#### Performance

- AAMA Rating: CW-PG-30 Size: 71x60
- Air Infiltration (CFM): 0.01
- Water Resistance (PSF): 6.24
- Structural (PSF): 60.2
- STC range: 30-36
- \*U-Factor: .45 / .37
- \*SHGC: .30 / .28
- \*VT: .53 / .48
- \*CRF: 55 / 51

\*NFRC simulation results from certified testing labs.  
Variety of glazing combinations available.



**Fight Village**  
Rochester, NY  
White Powder Coat



**Hillsdale Garden Apartments**  
San Mateo, CA  
Creme Powder Coat



**FairField Inn**  
Tulsa, OK  
White Powder Coat