

# Series 526C Horizontal Slider

CSI Division 08 51 13 - Aluminum Windows

12805 E. 31st St.  
Tulsa, OK 74146  
Phone: (800) 259-7580  
Fax: (918) 665-2197

## Style • Quality • Performance

### Standard Features

- Sealed 7/8-in. insulated glass for optimum thermal efficiency
- High-density pile weatherstripping with mylar fin
- 14 standard powder coat colors
- Full range of Anodized and AAMA 2605 finishes available
- Center cam locks plus hidden security locks
- Bronze rollers in nylon housing
- 2 5/8" and 3 1/4" frame depths available
- Interlocking meeting rails
- Extruded aluminum screen

### Performance

- AAMA Rating: CW-PG-40 Size: 72x60
- Air Infiltration (CFM): 0.02
- Water Resistance (PSF): 8.36
- Structural (PSF): 60.15
- STC range: 30-36
- \*U-Factor: .45 / .37.
- \*SHGC: .30 / .28
- \*VT: .53 / .48
- \*CRF: 55 / 51

\*NFRC simulation results from certified testing labs.  
Variety of glazing combinations available.



460 New York Ave  
Washington, DC  
Pewter Powder Coat



Coronado Drive Apartments  
Assisted Living  
Henderson, NV  
Bronze Powder Coat



Crystal City  
Arlington, VA  
Clear Anodized Class II



FairField Holiday Inn  
Acworth, GA  
Clear Anodized Class II