

Series 526D Horizontal Slider

CSI Division 08 51 13 - Aluminum Windows

12805 E. 31st St.
Tulsa, OK 74146
Phone: (800) 259-7580
Fax: (918) 665-2197

Style • Quality • Performance

Standard Features

- Sealed 7/8-in. insulated glass for optimum thermal efficiency
- High-density pile weatherstripping with mylar fin
- 14 standard powder coat colors
- Full range of Anodized and AAMA 2605 finishes available
- Center cam locks plus hidden security locks
- Bronze rollers in nylon housing
- 2 5/8" and 3 1/4" frame depths available
- Interlocking meeting rails
- Extruded aluminum screen

Performance

- AAMA Rating: CW-PG-70 Size: 71x60
- Air Infiltration (CFM): 0.08
- Water Resistance (PSF): 10.50
- Structural (PSF): 105
- STC range: 30-36
- *U-Factor: .45 / .37.
- *SHGC: .30 / .28
- *VT: .53 / .48
- *CRF: 55 / 51



*NFRC simulation results from certified testing labs.
Variety of glazing combinations available.



460 New York Ave
Washington, DC
Pewter Powder Coat

Coronado Drive Apartments
Assisted Living
Henderson, NV
Bronze Powder Coat

Crystal City
Arlington, VA
Clear Anodized Class II

FairField Holiday Inn
Acworth, GA
Clear Anodized Class II