

Series 700 Double Hung

CSI Division 08 51 13 - Aluminum Windows

12805 E. 31st St.
Tulsa, OK 74146
Phone: (800) 259-7580
Fax: (918) 665-2197

Style • Quality • Performance

Standard Features

- 3 1/4" frame depths available
- 14 standard powder coat colors
- Full range of Anodized and AAMA 2605 finishes available
- Lock-out tilt latches
- Operable sashes tilts in for easy cleaning
- Sealed 7/8" insulated glass for optimum thermal efficiency
- Extruded screen frame
- Carbon Steel spiral sash balances
- High-density pile weatherstripping with mylar fin
- Center camp locks plus hidden security locks

Performance

- AAMA Rating: CW-PG-30 Size: 56x91
- Air Infiltration (CFM): 0.16
- Water Resistance (PSF): 6.06
- Structural (PSF): 60.15
- STC range: 30-34
- *U-Factor: .49 / .41
- *SHGC: .28 / .26
- *VT: .51 / .47
- CRF: 59 / 56

*NFRC simulation results from certified testing labs.
Variety of glazing combinations available.



The Palace Apartments
Tulsa, OK
Bone White Powder Coat



Albertville High School
Albertville, AL
Bone White Powder Coat



Bennett Hall
Stillwater, OK
Creme Powder Coat