

Series 9950 Sliding Glass Door

CSI Division 08 32 13 - Aluminum Sliding Glass Door

12805 E. 31st St.
Tulsa, OK 74146
Phone: (800) 259-7580
Fax: (918) 665-2197

Style • Quality • Performance

Standard Features

- 4^{3/8}" frame depth
- 1" tempered insulated glass
- Impact-resistant glazing available
- 14 standard powder coat colors
- Full range of Anodized & AAMA 2605 finishes available
- Extruded screen frame
- Forced entry resistance grade 10
- XO, OX, OXO, OXXO and other operating configurations

Performance

- AAMA Rating: CW-PG-50 Size: 95"X83"
- Air Infiltration (CFM): 0.07
- Water Resistance (PSF): 12
- Structural (PSF): 75.19
- STC range: 35-36
- *U-Factor: .45 / .41
- *SHGC: .30 / .28
- *VT: .54 / .49
- CRF: 56 / 50

*NFRC simulation results from certified testing labs.
Variety of glazing combinations available.



The Catherine
Austin, TX
Clear Anodized Class II



The Lakes Residence Apartments
2622 W. Lake Minneapolis, MN
Dark Bonze & Champagne Anodized Class I



PerSie at Pike & Rose Apartments
Baltimore, MD
Clear Anodized Class I